

# HF106

1" - 60 W - 110 dB - 8 Ohm



## NOMINAL SPECIFICATIONS

Throat Diameter	25.4 mm (1 in)
Overall Diameter	95.7 mm (3.77 in)
180° Mounting Holes Diameter (2xM6)	76 mm (2.99 in)
Depth	58.8 mm (2.31 in)
<b>Net Weight</b>	<b>1.1 kg (2.3 lb)</b>
Shipping Box (Single carton box)	147 x 130 x 82 mm (5.8 x 5.1 x 3.2 in)
Shipping Weight	1.4 kg (3.1 lb)

## PART NUMBER

Faston Terminals - 8 Ohm Version	00444137
----------------------------------	----------

## NOTES:

Driver mounted on a **1" 50° x 40° Horn**  
**(1)** 2 Hour Test According to AES 2-1984 Rev. 2003  
**(2)** Maximum power is defined as 3dB greater than nominal power.  
**(3)** 12 dB/oct or higher slope high-pass filter  
**(4)** Averaged within the frequency range  
**(5)** The driver's exit coincides with the end of the phase plug, there is no adaptation throat.

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7 Ohm
AES Power Handling <b>(1)</b>	60 W
<b>Maximum Power Handling (2)</b>	<b>120 W</b>
Minimum Crossover Frequency <b>(3)</b>	1.3 kHz
<b>Sensitivity (1W/1m) (4)</b>	<b>110 dB</b>
Frequency Range	1.3-20 kHz
<b>Voice Coil Diameter</b>	<b>44 mm (1.73 in)</b>
<b>Winding Material</b>	<b>Al</b>
Former Material	Kapton
<b>Diaphragm Material</b>	<b>Ketone Polymer</b>
Diaphragm Shape	Annular
Winding Depth	2.3 mm (0.09 in)
Magnetic Gap Depth	2.6 mm (0.10 in)
Flux Density	2.1 T
Magnet	Neodymium Ring
Re	5.4 Ohm
Phase Plug Design	Annular
Exit Angle <b>(5)</b>	Combined Exit
NET Air Volume filled by HF Driver	0.25 dm^3 (0.009 ft^3)

