

ZXS10D2

Power Handling
400 Watts RMS / 800 Watts Max.

Technical Specifications

| | | |
|---------------------------|-------------|---------------------|
| Impedance | Zn | 2 x 2 Ohms |
| Voice Coil Diameter | Ø | 64 mm |
| Voice Coil Winding Height | | 35 mm |
| Max. Linear Excursion | Xmax | +/- 14 mm |
| Max. Mechanical Excursion | Xmax (Peak) | +/- 20 mm |
| Cone Area | Sd | 336 cm ² |
| Moving Mass | Mms | 177,1 g |
| DC Resistance | Re | 2 x 2 Ohms |
| Resonance Frequency | Fs | 26,5 Hz |
| Mechanical Q-Factor | Qms | 3,29 |
| Electrical Q-Factor | Qes | 0,6 |
| Total Q-Factor | Qts | 0,51 |
| Equivalent Air Volume | VAS | 32,2 L |
| Flux Density | B/L | 14,1 N/A |
| Efficiency 1W/1m | SPL | 84 dB |

Dual Voice Coil
Subwoofer 25 cm

Recommended Enclosure

Sealed Box
 Sealed Volume: 17 - 25 L

Compact

Recommended Enclosure

Ported Box
 Vented Volume: 35 L
 Port Diameter: 90 mm
 Port Area: 65 cm²
 Port Length: 42 cm
 Tuning Freq. (Fb): 34 Hz
 -3 dB Rolloff (F3): 28 Hz

Deep Tuning

Mechanical Components

- Steel Basket
- Non-pressed Paper Cone
- Foam Surround
- Injected PP Dustcap
- Single Polycot Spider
- Dual Magnet 2 x 42 oz (2.381 g)
- Magnet Size: Ø145 x 40 mm
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter: 260 mm
 Mounting Diameter: 228 mm
 Mounting Depth: 150 mm
 Shipping Weight: 7,1 kg

